

INFINITI Thermo

INFALLIBLE THERMAL INSULATION




smooth panel

- panel height 500 and 610 mm
- painting in any colour from the RAL palette/veneering in any colour from the veneer palette



panel with embossment

- panel height 500 and 610 mm
- painting in any colour from the RAL palette



- two gaskets ensuring better thermal insulation
- the shape of the panel serves as finger protection

Sectional garage doors with 60 mm panels


We created INFINITI Thermo with the needs of modern energy-efficient buildings in mind. We have combined the benefits of using panels with higher thermal insulation with a dedicated system of double-leaf chamber seals, thus creating a new reference point on the garage door market

Uw = 0,81

Heat transfer coefficient U [W/m²K] given for INFINITI Thermo sectional doors with dimensions of 5000 x 2500 mm. For gates without glazing, service doors, ventilation grilles.


Uw = 0,89

Heat transfer coefficient U [W/m²K] given for INFINITI Thermo sectional doors with dimensions of 2500 x 2250 mm. For gates without glazing, service doors, ventilation grilles.



Comfort and safety

INFINITI Thermo doors have extensive equipment that improves their durability, functionality and safety, and irreplaceable features that extend the service life.



photocell



silent rollers



integrated protection against spring breakage



double-leaf peripheral seal with a thermal chamber

all in one design

Create a design in the All in One system and get a consistent design for your garage door, doors, windows and window coverings.



